



ASPHALT ART

THE SOLUTION FOR OUTDOOR COMMUNICATION

AsphaltArt is designed to be used for short to midterm applications dependent on where the product is applied. The product can be used on asphalt, cement and untreated stone, pavement and many more surfaces.

The material can easily be removed from such surfaces. AsphaltArt is designed to be very robust against abrasion and other influences caused by normal use of the product. The special adhesive is designed to work outdoor on rough surfaces.



Uses

- Shop entries & stairways
- Bus, tramway or metro stations, airports
- Sport events: Motor sport events, marathons etc.
- Car, motorbike & general vehicle resellers
- Museums, meetings and other cultural events
- Petrol stations
- Car parks - indoor and outdoor including driveways
- Fast food drive through
- Sports stadiums
- Pedestrian areas

Features & Benefits

- High visual impact
- Easy to apply and remove
- Suitable for rough surfaces
- Slip resistant
- PVC free

info@continentalgrafix.com
www.asphaltart.com



ASPHALT ART

THE SOLUTION FOR OUTDOOR COMMUNICATION

Durability

The durability of AsphaltArt is dependent on the way the product has been applied – especially also on how it has been adjusted to uneven surfaces as well as on the surface in general on where it has been applied. We recommend a maximum use of 1–6 months. Furthermore, it also depends on the mechanical use of the surface where it is applied.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. Continental Grafix will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Printing method

UV curable inks and latex

Waste handling

AsphaltArt is designed to be fully recyclable. Used material and production waste can be handled as “aluminum waste”.

- Liquid varnish may extend life cycle

Technical information

Size	Width: 1.22 m Length: 10.16 m, 15.24 m, 30.48 m	
Material	Coated soft aluminum (polyurethane)	220μ +/- 10μ
Adhesive	Permanent acrylic solvent	80μ +/- 5μ
	Total weight	428 g/m ²
Certificates	Surfaces roughness (SRT)	55
	Slip-resistance	R12 / BS7976
	Flame resistance	M1 / F2
Application	minimum application temperature	+10°C / +50°F

Peel Adhesion to:	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	80oz/in (88N/100 mm)	50oz/in (55N/100mm)	70oz/in (77N/100mm)
24 hours dwell	100oz/in (110N/100 mm)	60oz/in (66N/100 mm)	80oz/in (88N/100 mm)

Chemical resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	I	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion
I = recommended for intermittent exposure only
NR = not recommended