



CAT / CLEAR WALK

MAKE INDOOR FLOOR AND WET AREA LOOK LIKE A CATWALK

CatWalk can be used for short to midterm applications. The material is applicable on various indoor surfaces. The foil consists of a dimension stable film with a textured resilient surface. The reverse side is coated with a pressure sensitive adhesive covered by a removable liner.

The product is provided with a resilient, durable and chemical resistance as well as a slip resistant surface for a large variety of applications. Moreover, the quick and easy portable product is extremely foot friendly. The waterproof adhesive and the therewith associated durability of the foil guarantee a versatile usability.

Features & Benefits

- Extremely secure with its slip-resistant surface
- Can be cut to shape
- Robust against abrasion
- Good chemical resistance
- Antibacterial surface - laboratory report from Quality Labs
- No lamination required

Uses

- Exhibitions
- Retail
- Leisure centres
- Swimming pools
- Saunas
- Point of purchase
- Supermarkets, shopping malls
- Pharmacies
- Bathrooms





CAT / CLEAR WALK

MAKE INDOOR FLOOR AND WET AREA LOOK LIKE A CATWALK

Durability

The durability depends on the way the product has been applied as well as on the condition of the surface and the amount and type of traffic on the area. We recommend a max 3 months use for indoor or wet area applications. Extended durability is possible when using a liquid laminate onto the printed area.

Storage

It is recommended to store the product in a closed packaging at a temperature of +15°C to +30°C and relative humidity between 45% and 60%. The product has a shelf life of 24 months after purchasing the material.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Printing method

UV curable inks, solvent, eco-solvent and latex

Waste handling

CatWalk can be burned after use and it is recommended to handle the production waste and the used material as industrial waste.

- Liquid varnish may extend life cycle

- Same product also available in clear as "ClearWalk" with higher tack

info@continentalgrafix.com
www.asphaltart.com

Technical information

Size	Width: 1.30 m	Length: 30.48 m
Material	vinyl foam	450μ +/- 5μ
Adhesive	clear acrylic adhesive	50μ +/- 5μ
Certificate	Slip-resistance	R10
Application	minimum application temperature	+10°C / +50°F

Peel Adhesion to:	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	55oz/in (66N/100 mm)	20oz/in (22N/100 mm)	40oz/in (44N/100 mm)
24 hours dwell	75oz/in (82N/100 mm)	25oz/in (27N/100 mm)	55oz/in (60N/100 mm)

Chemical resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	R	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion

I = recommended for intermittent exposure only

NR = not recommended

Further data

Coefficient of Friction (Kinetic) Dry / Wet	Rubber: 0,9 / 1,0 Leather: 0,3 / 1,0
Minimum application temperature	+10°C / +50°F**
Flammability	not tested

* Colour and lot variances of coated surfaces including paints, powder coatings, lacquers, stains and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface.

**At temperatures below +10 °C the surface has to be pre-treated with a gas burner.